



## 1" Alum-A-Like RD Blackout Blind Specification Sheet

<b>Headrail-Steel</b>	Size: 1" x 0.95" x 0.018" (26mm x 24mm x 0.45mm) Dimensions: Actual Width Color: Color Coordinated															
<b>Bottomrail-Steel</b>	Size: 0.795" x 0.374" x 0.018" (20.2mm x 9.5mm x 0.45mm) Color: Coordinated Dimensions: Stated Width Less 1/2" Lift Cord Route Hole: 6" O.C. From End Warning Label On Right Side Of Bottomrail Country Of Origin Tag At Center Of Bottomrail															
<b>Control Locations</b>	<table border="0" style="width: 100%;"> <tr> <td></td> <td style="text-align: center;"><b>20" Wide &amp; Over</b></td> <td style="text-align: center;"><b>16.5" Wide &amp; Over</b></td> </tr> <tr> <td>Lift Cord Route Hole:</td> <td style="text-align: center;">5.5" O.C. From End</td> <td style="text-align: center;">5" O.C. From End</td> </tr> <tr> <td>Tilt Rod Support Location:</td> <td style="text-align: center;">5.5" O.C. From End</td> <td style="text-align: center;">5" O.C. From End</td> </tr> <tr> <td>Cord Lock Location:</td> <td style="text-align: center;">4" O.C. From End</td> <td style="text-align: center;">3" O.C. From End</td> </tr> <tr> <td>Tilter Location:</td> <td style="text-align: center;">4" O.C. From End</td> <td style="text-align: center;">3" O.C. From End</td> </tr> </table>		<b>20" Wide &amp; Over</b>	<b>16.5" Wide &amp; Over</b>	Lift Cord Route Hole:	5.5" O.C. From End	5" O.C. From End	Tilt Rod Support Location:	5.5" O.C. From End	5" O.C. From End	Cord Lock Location:	4" O.C. From End	3" O.C. From End	Tilter Location:	4" O.C. From End	3" O.C. From End
	<b>20" Wide &amp; Over</b>	<b>16.5" Wide &amp; Over</b>														
Lift Cord Route Hole:	5.5" O.C. From End	5" O.C. From End														
Tilt Rod Support Location:	5.5" O.C. From End	5" O.C. From End														
Cord Lock Location:	4" O.C. From End	3" O.C. From End														
Tilter Location:	4" O.C. From End	3" O.C. From End														
<b>Slat-Room Darkening</b>	PVC-Room Darkening; Anti-Static; With 90% Opacity As Per Approved Sample Slat Width: 25mm (1") Dimensions: Actual Width Thickness: 0.45mm <span style="float: right;">Tolerance +/-0.04mm</span> Slat Count: 36" Drop = 43; 48" Drop = 58; 60" Drop = 72 72" Drop = 86; 84" Drop = 100 Braided Ladder: 21.3mm															
<b>Wand</b>	Clear Acrylic Plastic <span style="margin-left: 100px;">Solid Star Shaped; 8mm</span>															
<b>Other</b>	Color Coordinated slat clip <span style="margin-left: 100px;">Color Coordinated Bottomrail End Plugs</span> Color Coordinated Tassels <span style="margin-left: 100px;">(2 Tassels For 2 Cords; 3 Tassels For 3 Cords)</span> Cord Stops On All Lift Cords <span style="margin-left: 100px;">Clear Cord Lock</span> Clear Plastic Double Rivet Tilter <span style="margin-left: 100px;">W/Metal Gear</span>															
<b>Hardware</b>	Steel H/R Brackets <span style="margin-left: 100px;">Color Coordinated</span> <span style="margin-left: 100px;">Hex Head Screws; 1-1/4" Long</span> "U" Shaped Zinc Plated Steel Center Support Bracket															
<b>Packaging</b>	Instruction Sheet Packed W/Blind <span style="margin-left: 100px;">Warning Tag On Right Side Of Bottomrail</span> Bubble Pack On Both Ends <span style="margin-left: 100px;">Blind In Polybag</span> Wand Packed On Top Of Headrail <span style="margin-left: 100px;">Shrink Wrap On Cartons</span> Tassels Inside Of Headrail <span style="margin-left: 100px;">Blinds Up Yo 48" Wide Packed 6 Per Master</span> Carton Lable 2 Color <span style="margin-left: 100px;">Blinds Over 48" Wide Packed 4 Per Master</span> 1/4" Dia Blue Dot On Inner For Cord Stops <span style="margin-left: 100px;">1" Dia Blue Dot On Outer For Cord Stops</span>															

Blind Width	Ladders	Cords	Slat Clips	Center Supports	Screws	Buttons	Hold Downs
Up To 23"	2	2	2	0	9	2	2
24" - 29"	3	2	3	0	9	3	2
30" - 38"	3	2	3	0	9	3	2
39" - 44"	4	2	4	1	11	4	2
45" - 47"	4	2	4	1	11	4	2
48" - 63"	5	3	5	2	13	5	2
64" - 68"	5	3	5	3	15	5	2
69" - 84"	6	4	6	4	18	6	2
<b>Blind Width:</b>	16.5"	23" - 29"	Over 30" Wide				
<b>Wand Length:</b>	16"	21"	29"				
<b>Blind Drop:</b>	35"	48"	59" - 64"	71"	82"		
<b>Control Cord Length:</b>	25"	30"	35"	40"	45"		